

Mob: 9492032099

Email:rkunapareddy@yahoo.com

Date: 23.12.13

DIRECTOR

Telefax: 23156110

Off: 23158661 to 664, Ext: 1150

JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY Bureau of Industrial Consultancy services (BICS)

(Formerly Bureau of Industrial Consultancy and Research & Development) (BICARD) Kukatpally, Hyderabad – 500 085

Dr.K.RAMA MOHANA RAO

B.Tech (Civil) M.Tech (Struct), M.S., (Softwares) Ph.D.(I.I.T.D.), MIE, MISTE, MICI

Professor of Civil Engg. & DIRECTOR

To

The Principal

DAV School,

Vivekananda Nagar,

Hyderabad.

Sir,

Sub: JNTUH - BICS - Test report regarding the structural stability of DAV School Building, Vivekanandnagar, Hyderabad - Reg.

Ref: On request by Phone Dated: 16-12-2013

As per the reference cited above, JNTUH, BICS team comprising of Dr.K.RamaMohanaRao, Director, BICS, JNTUH, Dr.V.Venkateswara Reddy, Co-ordinator, BICS, JNTUH and technical staff were visited the above said site on dt.19.12.13 and tested the Junior Civil Judge Court Building with rebound hammer and UPV test. The test results are herewith enclosed.

MANAGER

D.A.V. PUBLIC SCHOOL

VIVEKANANDA NAGAR,

IKATPALLY, HYDERABAD, 500, 073

O.A.V. PUBLIC SCHOOL Vivekananda Nagar Colony, Kukatpally. HYDERABAD-500 0000

Stability Report of Junior Civil Judge Court Building and Judge Quarter in Kodad 1. INTRODUCTION:

On the request from the Deputy Engineer, R&B, Hyderabad concerned to DAV School experts from BICS, JNTUH, Hyderabad Prof.K. Rama Mohana Rao, Prof. V. Venkateswara Reddy and Raju visited the site of the DAV School Building at Vevekanand Nagar, Hyderabad. On enquiry it is found that the age of the structure is about 25 years. Based on the visual inspection, Cracks in the walls, and corrosion of reinforcement is observed in the Slab, Beams and Columns. Hence it was decided to do the non-destructive testing of the structure.

2. Salient Features of Court Building:

• Period of construction: 1988-1990

Framed Structure

Type of foundation: Isolated Footing

Date of Inspection: 19.12.2013

3. PHYSICAL OBSERVATIONS

- 1. Cracks observed in the wall and column joint.
- 2. Water stagnation marks on the roof.
- 3. Debris on the roof and sunshades
- 4. Blocking of rain water pipes

4. Non-Destructive tests:

The following Non-Destructive Tests were conducted to ascertain the present strength of the structure.

- a. Rebound Hammer Test.
- b. UPV Test

The results and observations of the test results are enclosed as under:


a. Rebound hammer test:

prince to secretary

Rebound hammer test is done to find out the compressive strength of concrete by using rebound hammer as per IS: 13311 (Part 2) – 1992. The underlying principle of the rebound hammer test is as follows:

The rebound of an elastic mass depends on the hardness of the surface against which its mass strikes. When the plunger of the rebound hammer is pressed against the surface of the concrete, the spring-controlled mass rebounds and the extent of such a rebound depends on the surface hardness of the concrete. The surface hardness and the rebound value are taken to be related to the compressive strength of the concrete. The rebound value is read from a graduated scale and is designated as the rebound number or rebound index. The compressive strength can be read directly from the graph

The typical graph for rebound hammer for the 3 directions of testing is given below:



The graph of the instrument is on the instrument itself.

Depending on the direction of testing the estimated compressive strength is calculated from the respective graph.

In case of columns and beams the testing is carried out by placing the Rebound hammer horizontally (perpendicular to the face of concrete) and in case of slabs (when tested from bottom) the Rebound Hammer is placed vertically upwards. Respective graph is used to ascertain the compressive strength of concrete.

Interpretation of results: Normally a minimum of 10 results are taken on a particular member at a specified location. The rebound hammer readings (called "R Value") are tabulated member wise.

D.A.V. PUBLIC SCHOOL

VIVEKANANDA NAGAR, KUKATPALLY, MYDERABAD-800 872. PRINCIPAL
D.A.V. PUBLIC SCHOOL
Vivekananda Nagar Colony,
Kukatpally,
HYDERABAD-500 072

The average of each group is first calculated. In case any particular R value in the group varies more than 5 units, the said values are discarded and then the Average R Value is calculated. With the average R value the strength and quality of concrete is estimated.

The tests were conducted by Schmidt Rebound test Hammer manufactures by M/s Schmidt, Switzerland (year of manufacture: Sept., 2009). All results are interpreted from the graphs provided by the Manufacturer.

b. Ultra Sonic pulse velocity test:

Ultra-Sonic pulse velocity t4ests are conducted on concrete structures to qualitatively access the concrete and to determine presence of any voids, cracks and other imperfections in concrete. In Ultra-sonic testing low frequency ultra sonic waves are transmitted through the concrete by the transmitter and are received at the other end by the receiver. The time taken by the pulse is measured and with the information of the thickness of concrete the instrument provides the velocity of the sound wave in Km/sec or m/sec. Based on the Pulse Velocity the quality of concrete is classified as per

IS Code: 13311 (Part 1) – 1992. The classification as per IS code is as under:

	Classification as per	r IS 13311 part 1
1.	Pulse Velocity (km/se	Concrete Quality
Tall.	10076 4.50	Excellent
2.	3.5 - 4.5	Good
3.	3.0 – 3.50	Medium
4.	Below 3.0	
	G.	Doubtful

UPV results provide the information on quality of the core concrete.

1 nicolium	y v	Y .	
Column			
1. Room No.30 (VIII /C) (350 x 380mm	1) 3.967 Km/sec	39	
2 Decare No. 20 (VIII (C) (250 200 1)			
2 Room No.30 (VIII /C) (350 x 380mm)		34	
3 Room No.30 (VIII /C) (350 x 380mm)			
Corridor	3.567 Km/sec	36	
4. Room No.29 (VIII /C) (350 x 380mm			
Corridor	3.666 Km/sec	35	
BEAM		U = 27.	
1. Room No.28 (VII/A) (230 x 600 mm)		36	
2. Room No.28 (VII /A) (230 x 600 mm	n) 4.019 Km/sec	38	
iii Column (350 x 380mm)			
1. Room No.31 Computer lab	3.592 Km/sec	36	
2 Poom No 21 Community			
2 Room No.31 Computer Lab	3.926 Km/sec	37	
3. Room No.31 Computer lab -Corridor		31	
4. Room No. 31 Computer Lab -Corridor	3.456 Km/sec	30	
BEAM			
1. Room No.28 (VII/A) (230 x 600 mm)		36	
2. Room No.28 (VII /A) (230 x 600 mm) 4.019 Km/sec	38	
II Second Floor-			
SOUTH WING			
i. Column			
1. Room No. 32 Library (350 x 380mm)		31	
2. Room No. 32 Library (350 x 380mm)	3.345 Km/sec	32	
BEAM			
1. Room No. 32 Library	3.326 Km/sec	35	
2. Room No. 32 Library	3.267 Km/sec	36	
ii Column			
1. Room No.34 IX A (350 x 380mm)	3.425 Km/sec	31	
2 Room No.34 IX A (350 x 380mm)	3.592 Km/sec	34	
3 Room No.34 IX A (350 x 380mm)			
Corridor	3.392 Km/Sec	35	7
4 Room No.34 IX A (350 x 380mm)			
Corridor	3.366 Km/sec	36	
BEAM	,	30	
1. Room No.34 IX A (230 x 600 mm)	3.72 Km/sec	37	
2. Room No.34 IX A (230 x 600 mm)	3.24 Km/sec	38	
iii Column	J. J	30	
1. Room No.35 IX B (350 x 380mm)	3.590 Km/sec	39	
2. Room No.35 IX B (350 x 380mm)	3.424 Km/sec	38	
3. Room No.35 IX B (350 x 380mm)	J. 12 - Killy Sec	30	
Corridor	3.245 Km/Sec	20	
4. Room No.35 IX B (350 x 380mm)	3.243 KIII/38C	30	
Corridor	3.556 Km/sec	24	
	3.336 KIII/Sec	31	
	Alas	العدي ()	
BEAM	Ship	Q aguera	

O.A.V. PUBLIC SCHOOL
VIVEKANANDA NAGAR,
KUKATPALLY, HYDERABAD-500 072

C A.V. PUBLIC SCHOOL Vivekananda Nagar Colony.
Kukatpally.
HYDERABAD-500 072

4. Room No.22 (VI D) -(350 x 380mm)	3.789 Km/sec	25	
Corridor	3.703 KIII/360	35	
BEAM			
1. Room No.21 (VI C) -230 x 600 mm)	3.576 Km/sec	21	
2. Room No.18 (VI C) -(230 x 600 mm)	3.678 Km/sec	31	
West Wing Column	3.076 KIII/SEC	39	
1. Room No.24 (VII A) -(350 x 380mm)	4.012 Km/sec	20	
2. Room No.24 (VII A) -(350 x 380mm)	4.112 Km/sec	39	
Column	4.112 Km/sec	40	
1. Room No.25 (VII B) -(350 x 380mm)	4.112 Km/sec	24	
2. Neem Nei23 (VII B) (330 x 380mm)	4.112 KIII/SEC	34	
2. Room No.25 (VII B)-(350 x 380mm)	4.012 Km/sec	25	
BEAM	4.012 Km/sec	35	
1. Room No.25 (VII B) (230 x 600 mm)	2 502 Vm/sss		
2. Room No.25 (VII B) -(230 x 600 mm)	3.592 Km/sec	37	
Column	3.604 Km/sec	34	
	2.752 //	92000	
1. Room No.26 (VII C) (350 x 380mm)	3.752 Km/sec	37	
2. Room No.26 (VII C) -(350 x 380mm)	2 604 Vm/see	20	
BEAM	3.694 Km/sec	36	19.
1. Room No.26 (VII C) (230 x 600 mm)	2 CO2 Voc/s		
2. Room No.26 (VII C) (230 x 600 mm)	3.692 Km/sec	34	
Column	3.707 Km/sec	35	
1. Room No.28 (VII/A) (350 x 380mm)	2.40 //		
1. NOOHI NO.28 (VII/A) (350 X 380mm)	3.40 Km/sec	30	
2. Room No.28 (VII/A) (350 x 380mm)	3.502 Km/sec	34	- min
3. Room No.28 (VII/A) (350 x 380mm)	3.302 Km/3cc	34	
Corridor	3.600 Km/sec	39	
4. Room No.28 (VII/A) (350 x 380mm)	3.000 Km/sec	39	
Corridor	3.492 Km/sec	25	
BEAM	3.492 Km/sec	35	
1. Room No.28 (VII/A) (230 x 600 mm)	2 E42 Vm/ses		
2. Room No.28 (VII/A) (230 x 600 mm)	3.542 Km/sec 3.562 Km/sec	34	
2. NOOII 140.28 (VII / A) (230 x 600 IIIII)	3.362 Km/sec	35	
North Side Wing			
i. Column			
1. Room No.29 (VIII /B) (350 x 380mm)	4.191 Km/sec	24	W 1500
1. Nooni No.25 (VIII / B) (530 x 380(IIIII)	4.131 // 260	34	
2 Room No.29 (VIII /B) (350 x 380mm)	4.100 Km/sec	35	
3 Room No.29 (VIII /B) (350 x 380mm)	nitoo kiii/ sec	33	
Corridor	4.196 Km/sec	37	-
4. Room No.29 (VIII /B) (350 x 380mm)	4.130 KHI/36C	3/	
Corridor	3.592 Km/sec '	30	
BEAM	3.332 MII/360	30	
1. Room No.28 (VII/A) (230 x 600 mm)	4.019 Km/sec	20	
2. Room No.28 (VII/A) (230 x 600 mm)	4.522 Km/sec	30	

Approximation of the state of t

1	CAM	1	I	1	1
	1. Room No.18 (V D) -(350 x 380mm)			36	
18	2. Room No.18 (V D) -(350 x 380mm)			30	
11	Column			30	
	1. Room No.23 Chemistry Lab	3.678 km/sec		31	
	2. Room No.23 Chemistry Lab	3.902 Km/sec		34	-
	3. Room No.23 Chemistry Lab	3.909 Km/sec		35	
	(Corridor Side)	olo ob Killy See		33	
	4. Room No.23 Chemistry Lab	3.514 km/sec		22	
	(Corridor Side)	3.314 KIII/36C		33	
1	Column				
	1. Room No.19 (VI A) -(350 x 380mm)	2.450.1/			
		3.459 Km/sec		36	
	2. Room No.19 (VI A) -(350 x 380mm)	3.501 Km/sec		37	
	3. Room No.19 (VI A) -(350 x 380mm) Corridor	3427 Km/sec		32	
	4. Room No.19 (VI A) -(350 x 380mm)	2.004 1/ /			
-	Corridor	3.904 Km/sec		39	
. 1	Column				
	1. Room No.20 (VI B) -(350 x 380mm)	2.672.1/			
	2. Room No.20 (VI B) -(350 x 380mm)	3.672 Km/sec		30	
+		3.527 Km/sec		34	
+	3. Room No.20 (VI B) -(350 x 380mm) Corridor	3.459 Km/sec		36	
-					
	4. Room No.20 (VI B) -(350 x 380mm) Corridor	3.6154 Km/sec		30	
-	BEAM		- m anam - la		
-					
	1. Room No.18 (V D) -230 x 600 mm)	3.972 Km/sec		30	
	2. Room No.18 (V D) -(230 x 600 mm)	3.992 Km/sec		34	
-					
1	Column				
. 1	1. Room No.21 (VI C) -(350 x 380mm)	3.998 Km/sec		32	
	2. Room No.21 (VI C) -(350 x 380mm)	3.667 Km/sec			
	3. Room No.21 (VI C) -(350 x 380mm)	3.604 Km/sec		31	
	Corridor	3.004 KIII/SEC		42	
-	I. Room No.21 (VI C) -(350 x 380mm)	3.742 Km/sec			
	Corridor	3.742 MII/SEC		40	
В	EAM				
1	. Room No.21 (VIC) -230 x 600 mm)	3.576 Km/sec		0.1	
	. Room No.18 (VI C) -(230 x 600 mm)	3.678 Km/sec	,	31	
	olumn	J.076 KIII/Sec		39	
-	Room No.22 (VI D) -(350 x 380mm)	2 650 Vm/s==			
2	Room No.22 (VI D) -(350 x 380mm)	3.659 Km/sec		31	
	Room No.22 (VI D) -(350 x 380mm)	3.660 Km/sec		34	
	orridor	3.761 Km/sec	•	34	

D.A.V. PUBLIC SCHOOL VIVEKANANDA NAGAR, KUKATPALLY, HYDERABAD-500 075 D.A.V. PUBLIC SCHOOL Vivekananda Nagar Colony, Kukatpally, HYDERABAD-500 072

	Folumn	1			
	1. Room No. 8			1	1
H	Stock Room (outer side)				
7	2. Room No. 8	3.576 Km/	sec	34	-
	Stock Room (outer side)			34	
	(outer side)	3.672 Km/s	sec	32	
	2 Column (350 x 380 mm)			32	
	V (A) (5)	4.47 Km/s	ec	38	
	(1)			38	
	-				
3	Column (350 x 380 mm)				
	Starts Poom (Page 1)	4.563 Km/ se	c Excellent	10	
-	Starts Room (Room No. 7)		- Accircut	40	42
4	Column				
-	Column				
-	V class A (5)				
-	V class A (5) class	3.95 Km/sec	Good		
5	Col. 1050		Good	39	41
	Column (350 x 380 mm)	4.274 km/sec	Excellent		
-	West Side near IV D Room	1	Lxcellent	39	41
_	Col				
6	Column (350 x 380 mm)	4.62 Km/ sec	Event		
	West wing near IV A Room	January See	Excellent	39	41
7					
7	Recently construction -4 year				
-	North wing- Stage platform				
-	column -(230 x 480)mm	3.55 km /sec	C 1		
		oloo kiii / sec	Good	25	17
8	Column- (230 x 480) mm	3.81 km/sec			
		J.OI KIII/SEC	Good	35	33
)	core Room -End Column	1.21 km/			IX.
	Back side (South side corner)	4.21 km/ sec	Excellent	30	25
				-	
)	Back side -End Column	1 20 km/			
_	Location-Medical Room	4.38 km/ sec	Excellent	37	37
	Beam (230 x 600mm)				
1	V Class Room			43	39
١	West Wing -Guest House		9		
E	Back side Room No-15				
	Near stair case column	2.024			
	COLUMN	3.031Km/ sec	Good	37	37
	. Room No.11 (IV C) -(350 x 380mm)	3.574 km/sec	100		
1 4					

D.A.V. PUBLIC SCHOOL
VIVEKANANDA NAGAR,
CUKATPALLY, HYDERABAD-500 878

D.A.V. PUBLIC SCHOOL Vivekananda Nagar Colony, Kukatpally, HYDERABAD-500 072

, , , , , , , , , , , , , , , , , , ,	3.910 Km/sec	1	31	
oom No.35 IX B (230 x 600 mm)			42	
Room No.35 IX B (230 x 600 mm)	3.890 Km/Sec		42	
v Col in			39	
1. Room No.37 (350 x 380mm)	3.590 Km/sec	Values not	33	
200 George 200 C	2.424 Km./222	MANAGEMENT MARKET	38	
2. Room No.37 (350 x 380mm)	3.424 Km/sec	given	38	
3. Room No.37 (350 x 380mm)	3.424 Km/sec			
4. Room No.35 IX B (350 x 380mm)	3.424 Km/sec			
WEST WING				
i. Column			34	
1. Room No. 39 IX D (350 x 380mm)	3.451 Km/sec			
2. Room No. 39 IX D (350 x 380mm)	3.462 Km/sec		35	
3. Room No. 39 IX D (350 x 380mm)	3.724 Km/sec		36	
ii Column				
1. Room No.44 XI (350 x 380mm)	3.392 Km/sec		30	
2 Room No.44 X I (350 x 380mm)	3.426 Km/sec		31	
3 Room No.44 XI (350 x 380mm)		74	p Alou-	
Corridor	3.512 Km/Sec		32	
4 Room No.44 XI A (350 x 380mm)				
Corridor	3.917 Km/sec		39	
iii Column				
1. Room No.44 XI (350 x 380mm)	3.329 Km/sec		31	
2. Room No.44 XI (350 x 380mm)	3.429 Km/sec		32	
3. Room No.44 XI (350 x 380mm)				
Corridor	3.529 Km/Sec		34	
4. Room No.44 XI (350 x 380mm)				
Corridor	3.602 Km/sec		39	
iv Column				
1. Room No.45 XII (350 x 380mm)	3.702 Km/sec		34	
2. Room No.45 XII (350 x 380mm)	3.412 Km/sec		35	
3. Room No.45 XII (350 x 380mm)	3.516 Km/sec		30	
4. Room No.45 XII (350 x 380mm)	3.810 Km/sec		39	
3EAM 1. Room No.45 XII	3.414 Km/sec		32	
2. Room No.45 XII	3.414 Km/sec		34	
2. ROOM NO.45 All				
Second Floor (West Wing)				
Location- Near Stair case				20
Column -(350 x 380)mm	4.160 km/ sec	Good	38	39
Location - Room No-43 X D				
North End column			24	16
Column- (350 x 380)mm	3.54km/sec	Good	24	10
2nd Floor Roof Slab			A ap	

D.A.V. PUBLIC SCHOOL
VIVEKANANDA NAGAR,
VIVEKANANDA NAGAR,
VIVEKANANDA NAGAR,
VIVEKANANDA NAGAR,

PRINCIPAL
D.A.V. PUBLIC SCHOOL
Vivekananda Nagar Colony,
Kukatpally,
HYDERABAD-500 072

1	North side Corner	2.99 km/ sec	Doubtful	27	25
2 .	South side				23
	South side corner	3.72 km / sec	Good	32	33
		1000			

Based on the above physical observations and test reports the building is suitable for use. As per your request you can add a light weight roof truss on the top floor by using light weight aerated bricks for partion and end walls.

In case of any clarifications please do contact us. Thanking you and assuring you of our best services.

Yours faithfully,

DIRECTOR, BICS

Mardy